

GRYPHON™ | GFS4400 2D

DATALOGIC

SIMPLE TO INTEGRATE

Designed for easy integration, the Gryphon GFS4400 2D module provides a 'plug-and-play' solution for system designers. Constructed using high-impact resin to withstand repeated cleanings with solvents and disinfectant solutions, the sealed enclosure meets industrial standards against water and particulates to provide dependable scanning performance.

ADVANCED IMAGING TECHNOLOGY

The GFS4400 2D OEM module features outstanding near-field reading, a wide angle field-of-view, high motion tolerance, snappy reading, and also offers excellent performance on decoding poor or damaged bar codes. As with all Gryphon readers, the GFS4400 reader offers good-read visual confirmation with Datalogic's patented 'Green Spot' technology.

RED ILLUMINATING LIGHT AND 4-DOT AIMER

User comfort is maximized with the GFS4400 OEM module's steady, deep red illumination light. Easier on the eyes than competitive products with flicker illumination, the highly visible 4-Dot aimer defines a precise reading zone and reduces accidental reads. The aimer's center cross provides a locator for targeted scanning in a multiple bar code environment.



FEATURES

- Highly visible 4-Dot aimer with center cross for targeted scanning
- Omnidirectional reading
- Advanced motion tolerance optics
- Image capture and document scanning capabilities
- Reads bar codes down to 4mils
- Reads 1D, 2D and Postal codes plus Stacked and Composite codes
- Interface options: RS-232 or USB
- Datalogic's patented 'Green Spot' for good-read feedback
- Integrated good-read beeper
- Automatic sensing or manual trigger options available
- High-impact resin creates a solvent-tolerant enclosure
- Water and Particulate Sealing Rating: IP54
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY - APPLICATIONS

- OEM Applications
- Service Kiosks
- Price Verifiers
- Ticket Readers
- Document Handling
- Medical Laboratories
- Vending Machines
- Additional Automated Equipment



GRYPHON™ | GFS4400 2D

TECHNICAL SPECIFICATIONS

DECODING CAPABILITY	
1D / Linear Codes	Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.
2D Codes	Aztec Code; China Han Xin Code; Data Matrix; MaxiCode; Micro QR Code; QR Code
Postal Codes	Australian Post; British Post; China Post; IMB; Japanese Post; KIX Post; Korea Post; Planet Code; Postnet; Royal Mail Code (RM4SCC)
Stacked Codes	EAN/JAN Composites; GS1 DataBar Composites; GS1 DataBar Expanded Stacked; GS1 DataBar Stacked; GS1 DataBar Stacked Omnidirectional; MacroPDF; MicroPDF417; PDF417; UPC A/E Composites

ELECTRICAL	
Current	Operating (Typical): < 180 mA Standby/Idle (Typical): Automatic Object Sense Mode: 115 mA Online & Serial OnLine Modes: 65 mA
Input Voltage	5 VDC +/- 5%

ENVIRONMENTAL	
Ambient Light	0 - 100,000 lux
Drop Resistance	Withstands repeated drops from 0.76 m / 2.50 ft onto a concrete surface
Humidity (Non-Condensing)	5 - 95%
Particulate and Water Sealing	IP54
Temperature	Operating: -20 to 50 °C / -4 to 122 °F Storage/Transport: -20 to 70 °C / -4 to 158 °F

INTERFACES	
Interfaces	OEM (IBM) USB; RS-232; USB: USB COM; USB HID Keyboard

PHYSICAL CHARACTERISTICS	
Colors Available	Grey; Other colors and custom logo options are available for minimum quantity purchase.
Dimensions	3.9 x 5.7 x 5.8 cm / 1.5 x 2.2 x 2.3 in
Weight (with Cable)	USB: 170 g / 6.3 oz RS-232: 204 g / 7.2 oz

READING PERFORMANCE	
Image Capture	Graphic Formats: BMP, JPEG, TIFF; Greyscale: 256, 16, 2
Image Sensor	Wide VGA: 752 x 480 pixels
Light Source	Aiming: 650 nm VLD
Print Contrast Ratio (Minimum)	25%
Reading Angle	Pitch: +/- 40°; Roll (Tilt): 180°; Skew (Yaw): +/- 40°
Reading Indicators	Beeper (Adjustable Tone); Datalogic 'Green Spot' Good Read Feedback; Good Read LED
Resolution (Maximum)	1D Linear: 0.102 mm / 4 mils Data Matrix: 0.178 mm / 7 mils PDF417: 0.102 mm / 4 mils

READING RANGES	
Typical Depth of Field	Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent. Code 39: 5 mil: 4.7 to 17.7 cm / 1.8 to 7.0 in Code 39: 10 mil: 1.7 to 33.2 cm / 0.7 to 13.1 in Data Matrix: 10 mil: 2.7 to 17.1 cm / 1.0 to 6.7 in Data Matrix: 15 mil: 1.2 to 24.6 cm / 0.5 to 9.7 in EAN: 13 mil: 2.5 to 41.9 cm / 1.0 to 16.5 in PDF417: 10 mil: 2.2 to 23.9 cm / 0.9 to 9.4 in QR Code: 10 mil: 3.5 to 16.0 cm / 1.4 to 6.3 in

SAFETY & REGULATORY	
Agency Approvals	The product meets necessary safety and regulatory approvals for its intended use. The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Environmental Compliance	Complies to China RoHS; Complies to EU RoHS
Laser Classification	Caution Laser Radiation - Do not stare into beam; IEC 60825, Class2

UTILITIES	
Datalogic Aladdin™	Datalogic Aladdin configuration program is available for download at no charge.
OPOS / JavaPOS	JavaPOS Utilities are available for download at no charge. OPOS Utilities are available for download at no charge.
Remote Host Download	Lowers service costs and improves operations.

WARRANTY	
Warranty	3-Year Factory Warranty

