

CITIZEN

Internal Peel & Rewind High-speed industrial printing



Space-saving design concept

The Hi-Open™ case lifts up vertically meaning that the printer's footprint does not change as the cover is opened making it ideal for tight spaces.

Front loading rewriter

The clever and unique CL-S700RII includes an internal rewriter that is simplicity itself to use. The front door drops down and the liner or labels are loaded.

Easy configuration

The large graphic LCD gives a clear indication of printer status and easy printer configuration.

CL-S700RII-CL-S703RII

Label, Industrial

Applications

- Courier
- Logistic / Transport
- Manufacturing
- Retail
- Warehousing



High performance with easy access

TOMORROW'S PRINTING TODAY

CITIZEN

Specifications

Model	CL-S700RII-CL-S703RII
Printing Technology	Thermal Transfer + Direct Thermal
Resolution	203 dpi, 300 dpi
Print Speed (maximum)	10 inches per second (254 mm/s), 8 inches per second (200 mm/s)
Print Width (maximum)	4 inches (104 mm)
Media Width (min to max)	1 to 5 inches (25.4 to 118.1 mm)
Roll Size (max), Core Size	Outside diameter 8 inches (200 mm) Core size 1 inch (25mm) Plus Outside media slot
Media Thickness (min to max)	63.5 to 254 µm
Media Length (min to max)	0.25 to 99.99 inches (6.35 to 2539.74mm)
Media Sensor	Fully adjustable rear sensor and high resolution front sensor
Main Interface	Triple interface USB, parallel and serial built-in, exchangeable interface card slot for optional card
Interface	Wireless LAN 802.11b and 802.11g standards, 100 metres, 64/128 bit WEP, WPA, up to 54Mbps, Ethernet (10/100 BaseT)
Ribbon size	3.4 inches (86.5 mm) maximum outside diameter. 450 metres length.
Ribbon winding & type	Ink side in or out, automatically sensing. Wax, Wax/Resin or Resin Type
Ribbon system	ARCP™ automatic ribbon tension adjustment
Mechanism	Hi-Lift™ metal mechanism with wide opening head

CL-S700RII-CL-S703RII

Label, Industrial

Features & Benefits

- Hi-Open™ case for vertical opening, no increase in footprint and safe closing.
- No more unreadable labels - the ARCP™ ribbon control technology assures clear prints.
- ENERGY STAR® compliant
- Recyclable packaging



Ingeniously designed for easy operation and reliability

CITIZEN

CL-S700RII-CL-S703RII

Label, Industrial

Model	CL-S700RII-CL-S703RII
Control panel	4 buttons, 4-line back-lit graphic LCD
Emulations (Languages)	Cross-Emulation™ - automatic switching between Zebra® ZPL-II® and Datamax® I-Class®, DMX400, Datamax® I-Class™ & DMX400™, Zebra® ZPL-II®, BASIC interpreter for data stream processing, Eltron®, EPL-2®, Citizen Original Commands
Drivers and software	Free-of-charge on CD with printer, including support for various platforms
Flash (Non-Volatile Memory)	16 MB total, 4MB available for user
Size (W x D x H) and Weight	255 x 490 x 385 mm, 17.6 Kg
Warranty	2 years on printer. 6 months or 50 Kms printhead

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0