

# CITIZEN

## Cost-effective 4-inch POS printing with precise document scaling

Superior performance and reliability with dynamic functionality



### Compression driver

Equipped with a compression driver the CT-S4500 can scale down A4 documents and print them perfectly on 4-inch receipt paper.

### Well connected

With a USB interface as standard as well as optional Bluetooth, Serial, LAN or WiFi - the CT-S4500 is perfect for various applications.

### Stylish design

The CT-S4500 is ideal for premier locations where eye-catching design meets state-of-the-art POS printing. Choose between the pure white and stylish black versions.

## CT-S4500

POS, Receipt printer (thermal 4 inch)

### Applications

- Hospitality
- Kiosk
- Retail
- Betting
- Rental / Hiring



High opening case for quick and easy drop-in media loading

TOMORROW'S PRINTING TODAY



USB as standard with optional Bluetooth, Serial, LAN or WiFi available

## Specifications

## CT-S4500

**POS, Receipt printer (thermal 4 inch)**

### Features & Benefits

- Paper exit: Front exit - prevents damage from moisture or foreign objects
- Paper load: Easy paper loading
- Printing Speed: Fast print out of receipts - up to 200mm per seconds
- Mobile-POS ready
- A4 printer replacement - compress driver scales down documents
- ENERGY STAR® compliant
- Small footprint
- Tool-free maintenance



Sophisticated and sleek design

# CITIZEN

CT-S4500

POS, Receipt printer (thermal 4 inch)

<b>Model</b>	<b>CT-S4500</b>
<b>Printing Technology</b>	Direct Thermal
<b>Resolution</b>	203 dpi
<b>Print Speed (maximum)</b>	200 mm /sec.
<b>Print Width (maximum)</b>	104 mm
<b>Media Width (min to max)</b>	58 - 112 mm
<b>Roll Size (max), Core Size</b>	102 mm outside diameter
<b>Media Thickness (min to max)</b>	65 to 150 µm
<b>Media Sensor</b>	Gap, reflective black mark and paper end
<b>Main Interface</b>	USB 2.0 full speed
<b>Interface</b>	Bluetooth with Apple™ MFi compatibility, Serial (RS-232C compliant), Compact Wireless LAN, Ethernet, USB with hub, Ethernet + USB host
<b>Power supply</b>	100 - 240V, 50/60hz
<b>Control panel</b>	1 button, 2 LEDs
<b>Emulations (Languages)</b>	ESC/POS™
<b>Drivers and software</b>	Free-of-charge from website, including support for various platforms
<b>Flash (Non-Volatile Memory)</b>	384K bytes
<b>Size (W x D x H) and Weight</b>	170 x 216 x 151 mm, 2.5 Kg
<b>Cutter</b>	Guillotine type, full and partial
<b>Warranty</b>	2 years including head and cutter
<b>EMC and safety standards</b>	CE, UL, C-UL, FCC, VCCI

All product names are trademarks of the respective manufacturers. Zebra®, ZPL and EPL are trademarks of ZIH Corp. Datamax® is a trademark of Datamax-O'Neil Corporation. Designs, specifications and availability are subject to change without notice. Errors and omissions excluded. © Citizen Systems Europe GmbH, V.1.0